



XTHPS21

Systemkonfiguration	Infra-Bass
Belastbarkeit RMS	1500 W
Frequenzgang	(-3 dB) 25÷70 Hz
Peak SPL (@1 m)	139 dB
Nennimpedanz	8 Ohm
Lautsprecher	LF 1x21" neodymium
Eingänge	2xNL4FC Speakon
Cabinet	Birke
Maße (WxHxD)	820x600x800 mm
Netto-Gewicht	59.5 kg



XTHPS33

Systemkonfiguration	Bass
Belastbarkeit RMS	2200 W
Frequenzgang	(-3 dB) 30÷150 Hz
Peak SPL (@1 m)	142 dB
Nennimpedanz	4 Ohm
Lautsprecher	LF 1x15" neodymium LF 1x18" neodymium
Eingänge	2xNL4FC Speakon
Cabinet	Birke
Maße (WxHxD)	580x1170x620 mm
Netto-Gewicht	68 kg



XTHPS36

Systemkonfiguration	Bass
Belastbarkeit RMS	2400 W
Frequenzgang	(-3 dB) 30÷150 Hz
Peak SPL (@1 m)	143 dB
Nennimpedanz	4 Ohm
Lautsprecher	LF 2x18" neodymium
Eingänge	2xNL4FC Speakon
Cabinet	Birke
Maße (WxHxD)	1170x580x800 mm
Netto-Gewicht	84 kg